

# ADSL2/2+ CT-5071T

Single Ethernet Port



The CT-5071T is a high-performance ADSL2+ Ethernet Router that features one 10/100 Base-T Ethernet port and one ADSL2+ port for broadband Internet access at speeds of up to 24 Mbps over a regular telephone line. The CT-5071T has full routing capabilities to segment and route IP packets. It also features advanced technologies, such as Stateful Firewall, NAT (Network Address Translation), and TR-069 Remote Management.

## FEATURES

---

### Fast Connections

The ADSL2/2+ port carries WAN traffic at speeds of up to 24 Mbps (ADSL2+), while the LAN port supports LAN traffic at speeds up to 100 Mbps. The TR-068 compliant rear panel and LED indicators also simplify installation and improve ease-of-use.

### Secure Connections

As the first level of protection, a Stateful Firewall (with DoS protection) and NAT/PAT help to isolate the LAN from external threats. Second, IP and MAC address filtering provide fine-grained access control to or from the network. Third, advanced security technologies, such as Virtual Private Networks (VPN) with PPTP pass-through, L2TP pass-through and IPSec pass-through ensure secure networking.

### Reliability and Quality

For over 20 years Comtrend has delivered superior quality products to our customers worldwide. Every product goes through rigorous testing, and is backed by a 2 year warranty.

### Remote Auto-Configuration (TR-069)

TR-069/TR-098/TR-111 standards compatibility ensures interoperability with central office remote management equipment. From the user perspective this reduces downtime and frustration. For the service provider it means improved customer relations and simplified management.

### Flexible Management Toolkit

Besides TR-069 remote management, other supported tools include telnet, ssh and a web user interface. These all allow for complete configuration and control including firmware upgrades (via FTP/TFTP) and configuration backup/restoration. The web user interface features auto-PVC configuration, a diagnostic dashboard and other advanced management functionality.

# CT-5071T

Single Ethernet Port



## SPECIFICATIONS

### Hardware

- RJ-11 X1 for ADSL
- RJ-45 X 1 for LAN
- Reset Button X 1
- Power switch X 1

### WAN

- Comply with ITU-T G.992.5, ITU-T G.992.3, ITU-T G.992.1, ANSI T1.413 Issue 2
- G.992.5 (ADSL2+):
  - Downstream : 24 Mbps Upstream : 1.3 Mbps
- G.992.3 (ADSL2)
  - Downstream : 12 Mbps Upstream : 1.3 Mbps
- G.DMT
  - Downstream : 8Mbps Upstream : 832kbps
- AnnexM

### LAN

- IEEE 802.3, IEEE 802.3u
- 10/100 BaseT auto-sense
- Support MDI/MDX

### ATM Attributes

- RFC 2364 (PPPoA), RFC 2684 (RFC 1483) Bridge/Route; RFC 2516 (PPPoE); RFC 1577 (IPoA); Annex M
- Support 8 PVCs
- AAL5
- UBR/CBR/VBR
- UNI 3.1/4.0
- OAM F4/F5

### Management

- SNMP, Telnet, Web-based management, Configuration backup and restoration
- Software upgrade via HTTP, TFTP server, or FTP server
- Supports TR-069/TR-098/TR-111 for Remote Management

### Bridge Functions

- IEEE 802.1d
- VLAN support
- Spanning Tree Algorithm
- IGMP Proxy

### Routing Functions

- Static route, RIP, and RIPv2, NAT/PAT, DHCP Server/DHCP Relay, DNS Proxy, ARP

### Security Functions

- PAP, CHAP, TCP/IP/Port filtering rules, Port triggering/Forwarding, Packet and MAC address filtering, access control, SSH

### QoS

- L3 policy-based QoS, IP QoS, ToS

### Application Passthrough

- PPTP, L2TP, IPSec, VoIP, Yahoo messenger, ICQ, RealPlayer, NetMeeting, MSN, X-box, etc

### Power Supply

- 100 Vac -220 Vac,

### Environmental Condition

- Operating temperature: 0 ~ 50 degrees Celsius
- Relative humidity: 5 ~ 95% (non-condensing)

### Dimensions

- 92mm(W) X 34mm(H) X 114mm(D)

### Kit Weight

- 1\* CT-5071T, 1\*RJ11 cable, 1\*RJ45 cable, 1\*power adapter, 1\*CD-ROM = 0.65 kg

Note: Specifications are subject to change without notice



**COMTREND CORPORATION**

**Taiwan:**  
3F-1, No.10, Lane 609, Chung Hsin Road Section 5, San Chung, Taipei, Taiwan 24159  
Tel: 886-2-2999-8261  
Fax: 886-2-2999-8497

**China:**  
NO.88 East QianJin Road,Kunshan City,JiangSu,China  
Tel: 86-512-57383156, 86-512-57383157,  
86-512-57384515  
Fax: 86-512-57383155

**Spain:**  
Edif. América II C/Prócion,7 portal 3 bajo H 28023 Madrid, Spain  
Tel: 34-917990403  
Fax: 34-913510999

**UK:**  
566 Chiswick High Road Building 3, Chiswick Park Chiswick - London, W4 5YA UK  
Tel: 44-0-8453701031  
Fax: 44-0-8453701032

**France:**  
87, Rue du Gouverneur Général Félix Eboué 92130 Issy-les-Moulineaux, France  
Tel: 33-1-70715700  
Fax: 33-1-70715701

**Czech Republic:**  
TOKOVO Jankovcova 1518/2, 170 00, Prague 7, Czech Republic  
Tel: 420-266-782040  
Fax: 420-266-782990

**USA & Canada:**  
16 Goodyear, Suite 120, Irvine, CA 92618  
Tel: 1-949-7539640  
Fax: 1-949-7539020

**Brazil:**  
Al. Campinas, 977 - 7º. Floor - Room 71 / 72 - Jardins  
Zip Code: 01404-001 - São Paulo - SP - Brazil  
Tel: 00 55 11 3052-2295  
Fax: 00 55 11 3052-2295

**Mexico:**  
Mariano Escobedo 396 Office 503 Colonia Anzures, Deleg. Miguel Hidalgo 11590 Distrito Federal México  
Tel: +52 (55) 4623-1516