

ADSL2/2+

4 Ethernet Port | WiFi

CT-5367

Wireless Router



The CT-5367 is a solid ADSL2/2+ platform with all the essentials needed for fast and reliable DSL service. With unrivalled ease of use, you can quickly extend and control your local area network over four 10/100 Base-T Ethernet ports and an integrated 802.11g wireless Access Point (AP) with Wi-Fi Protected Setup (WPS).

FEATURES

ADSL2/2+

The CT-5367 allows for aggregate bandwidth of 24 Mbps in ADSL2+ mode and 12 Mbps in ADSL mode in the downstream.

High Performance WiFi

Wireless Local Area Networking (WLAN) at speeds of up to 54 Mbps is provided with an integrated 802.11b/g Access Point (AP).

Supports TR-069/TR-098/TR-111 for remote management

TR-069/TR-098/TR-111 standard compatibility ensures interoperability with central office remote management equipment. From the user perspective this reduces downtime and frustration. For the service provider it means improved customer relations and cost savings.

Quality Of Service (QoS)

Classify, control, and prioritize diverse traffic types, assuring pristine video, toll-quality voice, and error-free data.

Wi-Fi Protected Setup (WPS)

For greater ease of use, WPS is packaged with this device. WPS enables fast and secure wireless setup with the push of a button.

Reliability and Quality

For over 20 years Comtrend has delivered superior quality products to our customers worldwide. Every product goes through rigorous testing, and is backed by a 2 year warranty.

CT-5367

4 Ethernet Port | WiFi



SPECIFICATIONS

Hardware

- RJ-11 X1 for ADSL,
- RJ-45 X 4 for LAN,
- WPS X1,
- Reset Button X 1,
- Power switch X 1,
- WiFi Antenna X1

WAN

- Comply with ITU-T G.992.5, ITU-T G.992.3, ITU-T G.992.1, ANSI T1.413 Issue 2
- G.992.5 (ADSL2+):
Downstream : 24 Mbps Upstream : 1.3 Mbps
- G.992.3 (ADSL2)
Downstream : 12 Mbps Upstream : 1.3 Mbps
- GDMT
Downstream : 8Mbps Upstream : 832kbps
- AnnexM

LAN

- IEEE 802.3, IEEE 802.3u
- 10/100 BaseT auto-sense
- Support MDI/MDX

Wireless

- IEEE802.11b/g
- 64, 128-bit Wired Equivalent Privacy (WEP) Data Encryption
- 11 Channels (US, Canada) / 13 Channels (Europe) / 14 Channels (Japan)
- Up to 54Mbps data rate
- WPA/WPA2
- IEEE 802.1x
- Afterburner mode/Turbo mode(Optional)
- RF operating Frequency: 2.412-2.497GHz (2.4GHz ISM Band)
- RF output power: 15dBm
- Antenna gain: 2dBi

ATM Attributes

- RFC 2364 (PPPoA), RFC 2684 (RFC 1483) Bridge/Route; RFC 2516 (PPPoE); RFC 1577 (IPoA)
- Support 8 PVCs
- AAL5
- UBR/CBR/VBR
- UNI 3.1/4.0
- OAM F4/F5

Management

- SNMP, Telnet, Web-based management, Configuration backup and restoration
- Software upgrade via HTTP, TFTP server, or FTP server
- Supports TR-069/TR-098/TR-111 for Remote Management

Bridge Functions

- IEEE 802.1d
- VLAN support
- Spanning Tree Algorithm
- IGMP Proxy

Routing Functions

- Static route, RIP, and RIPv2, NAT/PAT, DHCP Server/DHCP Relay, DNS Proxy, ARP

Security Functions

- PAP, CHAP,
- TCP/IP/Port filtering rules, Port triggering/Forwarding, Packet and MAC address filtering, access control, SSH

QoS

- L3 policy-based QoS, IP QoS, ToS

Application Passthrough

- PPTP, L2TP, IPSec, VoIP, Yahoo messenger, ICQ, RealPlayer, NetMeeting, MSN, X-box, etc

Power Supply

- 100 Vac -240 Vac, 18Vdc/0.5A

Environment Condition

- Operating temperature: 0 ~ 50 degrees Celsius
- Relative humidity: 5 ~ 95% (non-condensing)

Kit Weight

1*CT-5367/u, 1*RJ11 cable, 1*RJ45 cable, 1*power adapter, 1*CD-ROM = 1 kg



COMTREND CORPORATION

Taiwan:

3F-1, No.10, Lane 609, Chung Hsin Road Section 5, San Chung, Taipei, Taiwan 24159
Tel: 886-2-2999-8261
Fax: 886-2-2999-8497

China:

NO.88 East QianJin Road, Kunshan City, JiangSu, China
Tel: 86-512-57383156, 86-512-57383157, 86-512-57384515
Fax: 86-512-57383155

Spain:

Edif. América II C/Prócion,7 portal 3 bajo H 28023 Madrid, Spain
Tel: 34-917990403
Fax: 34-913510999

UK:

568 Chiswick High Road Building 3, Chiswick Park Chiswick - London, W4 5YA UK
Tel: 44-0-8453701031
Fax: 44-0-8453701032

France:

87, Rue du Gouverneur Général Félix Eboué 92130 Issy-les-Moulineaux, France
Tel: 33-1-70715700
Fax: 33-1-70715701

Czech Republic:

TOKOVO Jankovcova 1518/2, 170 00, Prague 7, Czech Republic
Tel: 420-266-782040
Fax: 420-266-782990

USA & Canada:

16 Goodyear, Suite 120, Irvine, CA 92618
1-949-7539640
Fax: 1-949-7539020

Brazil:

Al. Campinas, 977 - 7º. Floor - Room 71 / 72 - Jardins
Zip Code: 01404-001 - São Paulo - SP - Brazil
Tel: 00 55 11 3052-2295
Fax: 00 55 11 3052-2295

Mexico:

Mariano Escobedo 396 Office 503 Colonia Anzures, Deleg. Miguel Hidalgo 11590 Distrito Federal México
Tel: +52 (55) 4623-1516