

DOCSIS 3.0 4X4 5GHz GATEWAY with MoCA

Intel® Puma™ 6 DOCSIS 3.0 32x8. 4x4 5GHz Wave2 MIMO and 3x3 2.4GHz dual band Wi-Fi, MoCA 2.0, GigE, USB



KEY FEATURES

- Certified DOCSIS 3.0 32x8 channel bonding
- Wi-Fi 4x4 5GHz 802.11ac Wave 2 MIMO and 3x3 2.4GHz 802.11n dual band concurrent internal antennas
 - 32 SSIDs (16 SSIDs per radio)
 - Individual configuration for each SSID (security, bridging, routing, firewall and Wi-Fi parameters)
- MoCA for highest performance
- Two USB 2.0 host, supporting Network Attached Storage (NAS) functionality
- Integrated DLNA Media Server with support for video, audio and image serving
- Extensive operator control via configuration file and SNMP
- TR-069 and HNAP for easy setup and remote management

FAST WAN AND LAN CONNECTION

The CGNVM-3582 has the capacity to receive 1.2Gbps (32x8) over its DOCSIS interface with thirty-two bonded channels. The integrated Wi-Fi 4x4 5GHz 802.11ac Wave 2 MIMO and 3x3 2.4GHz 802.11n dual band access point significantly improves customer experience extending range and coverage with blazing speeds. For wired clients, the four Gigabit Ethernet ports offer ultra-fast connections. MoCA 2.0 provides another extension option.

IPV4/IPV6 DUAL STACK SUPPORT

The CGNVM-3582 supports full IPv4 routing features, as well as full support for IPv6 routing and firewall. The CGNVM-3582 supports both DSLite as well as 6RD for different IPv6 deployment and transition strategies.

EASY SECURE WIRELESS NETWORKING

The CGNVM-3582 supports pre-configured and pre-enabled Wi-Fi security via Wi-Fi Protected Setup (WPS), allowing the end-user to rapidly set up a secure wireless network without manual configuration. Hitron's AutoSync software provides secure automated setup of extenders in the customer's home or business.



SPECIFICATIONS

Connectivity

- RF F-type 75Ω female connector
- 4x RJ-45 Ethernet port 10/100/1000Mbps
- 2x USB 2.0 Type A connector with Host interface

Management

- Protocol support: TR-069, HNP & SNMP v1, v2C, v3
- Web-based GUI control configuration and management
- Power-on self diagnostic
- Hitron proprietary MIBs for extended support on DOCSIS, router management, Wi-Fi management and MoCA management

Reception-Demodulation

- DOCSIS/EuroDOCSIS 3.0/2.0/1.1
- DOCSIS 3.0 demodulation: 64QAM, 256QAM
- DOCSIS 3.0 data rate: Up to 1.2Gbps with 32 bonded downstream channels
- Frequency (edge-to-edge): 108-1002MHz
- Channel bandwidth: 6MHz (DOCSIS, DOCSIS-J); 8MHz (EuroDOCSIS); 6/8MHz (dual mode)
- Signal level: -15dBmV to 15dBmV

Transmitter-Modulation

- DOCSIS/EuroDOCSIS 3.0/2.0/1.1
- DOCSIS 3.0 modulation: QPSK, 8QAM, 16QAM, 32QAM, 64QAM, and 128QAM (SCDMA only)
- DOCSIS 3.0 data rate: Up to 320Mbps with 8 bonded upstream channels
- Frequency: 5-85MHz

MoCA 2.0 Reception / Transmitter-Modulation

- Demodulation/Modulation: BPSK, QPSK, 8QAM, 16QAM, 32QAM, 64QAM, 128QAM, 256QAM, 512QAM, 1024QAM
- PHY data rate: 700Mbps (baseline mode)
- Throughput: 400+Mbps (baseline mode) / 500+Mbps (turbo mode, point to point) / 800Mbps (bonding channel)
- Frequency range: 1025 ~ 1625 MHz
- Channel bandwidth: 100MHz (baseline mode)

Environmental

- Operating temperature: 0°C (32°F) - 40°C (104°F)
- Operating humidity: 10% - 90% (non-condensing)
- Storage temperature: -40°C (-40°F) - 70°C (158°F)

Compliance Certificates

- FCC, IC, UL, Wi-Fi Alliance
- RoHS compliant
- CableLabs

Routing Support

- Protocol support: IGMP v3 for IPTV service capability
- MAC address filtering (IPv4/IPv6)
- IP source/destination address filtering (IPv4/IPv6)
- DHCP, TFTP and ToD clients (IPv4/IPv6)
- DHCP server supports RFC 1541 (IPv4)
- DHCPv6 obtains prefix from DHCPv6 server through prefix delegation
- Firewall with stateful inspection (IPv4/IPv6)
- Hacker intrusion prevention and detection
- Application content filtering (IPv4/IPv6)
- VPN termination and pass through (IPv4/IPv6)
- Complete NAT software implemented as per RFC 1631 with port and address mapping (IPv4)
- DSLite support for IPv4 in-home support with IPv6 MSO backbone
- 6RD support for quick IPv6 deployment over IPv4 backbone
- RIP2 for Static IP support

Wireless

- 802.11a/b/g/n/ac
- 4T4R 5GHz 802.11ac Wave 2 MIMO + 3T3R 2.4GHz 802.11n dual band concurrent with 450Mbps+1733Mbps PHY data rate
- 20/40/80/160MHz channel bandwidth
- Up to 16 SSIDs for each frequency
- Security: WEP-64/WEP-128, WPA-PSK/WPA2-PSK (TKIP/AES), WAPI
- QoS: WMM/WMM-PS
- WPS (Wi-Fi Protected Setup) PBC, PIN
- Fast roaming: 802.11r/k/v and Band Steering (BS)
- Wi-Fi output power range (FCC):

• 2.4G (EIRP)	29.97 / 27.97dBm
• 5G Uni 1 (EIRP)	27.52 / 23.52dBm
• 5G Uni 2 (EIRP)	27.52 / 23.52dBm
• 5G Uni 3 (EIRP)	27.02 / 23.02dBm
• 5G Uni 4 (EIRP)	27.12 / 23.12dBm

Mechanical

- 8 status LEDs (Power, DS, US, Status, Eth, Wi-Fi 2.4G, Wi-Fi 5G, MoCA)
- WPS button
- Factory reset button
- Dimensions: 120mm (W) x 120mm (H) x 202.9mm (D)
- Weight: 800g ± 10g

Electrical

- Power: 100-120VAC, 50/60Hz
- Power consumption: 5W (power save mode), 18W (typical), 36W (maximum)
- Surge protection: RF input sustains at least 4KV, Ethernet RJ-45 sustains at least 4KV, Voice sustains at least 1.5KV

